

# HOT SHOTS (Four Cylinder Front-Wheel Drive Cars) 2024 TECHNICAL RULEBOOK

## **GENERAL CLASS RULES:**

1. This is a STOCK class. Everything must be stock unless stated otherwise in the rules listed below. If it is not stock, it is not legal.

## CARS:

- 1. Cars must have a complete stock body with stock frame and suspension components in stock location. Hulling is only permitted on the driver's side door for the roll cage.
- 2. Low profile cars such as Camaros, Firebirds, Mustangs, etc. are not allowed.
- 3. Wheelbase: Minimum 96", Maximum 105".
- 4. Front and rear tow hooks are required for wrecker purposes.

#### **ENGINE:**

## SENOIA ENGINE RULES IN GENERAL RULES ALSO APPLY

- 1. MUST be stock for make. (Chevrolet in Chevrolet, etc.)
- 2. Only four cylinder engines are allowed.
- 3. Stock exhaust must run past the driver's door.
- 4. Stock air filter and breather.
  - K&N Air Filter allowed. Must run stock air tube.
- 5. Stock ignition.
- 6. Alternator must be working and in its original position.
- 7. Battery must be securely mounted in its original position.
- 8. Stock wiring harness is required.
- 9. No modifications can be made.
- 10. Superchargers are not allowed.
- 11. You must have a copy of the owner's manual for the specific car you are racing.
- 12. Header is allowed, but must add 50 pounds.

## **EXHAUST - MUFFLERS ARE REQUIRED AT SENOIA RACEWAY**

1. Stock exhaust only; must have muffler.

#### TRANSMISSION:

1. Stock automatic or stock standard transmission.

## **DRIVELINE:**

- 1. Only front-wheel drive cars are permitted.
- 2. All-Wheel drive cars are not allowed.
- 3. Rear-wheel drive cars are not allowed.
- 4. Driveline must be stock for make and model.
- 5. Differential lock permitted.

#### **BRAKES:**

- 1. Must remain stock for make and model of car.
- 2. No adjusters are allowed.

## SUSPENSION AND FRAME:

#### SENOIA SUSPENSION RULES IN GENERAL RULES APPLY

- 1. No altering in any way.
- 2. Stock shocks in stock locations.
- 3. No adjustable or aluminum shocks.

#### **BODY:**

- 1. Two-door or four-door cars are allowed.
- 2. All glass must be removed. Lexan windscreen may be used if desired.
- 3. The back seat may be removed, but any opening must be covered with metal.
- 4. Doors must be welded or chained shut.
- 5. No hulling of right-side doors and trunk area. If hulling is done, 100 lbs. will be added to the total weight.
- 6. No cutting of the body is allowed.

#### **ROLL CAGE AND SAFETY:**

#### SENOIA SAFETY RULES IN GENERAL RULES ALSO APPLY

- 1. A four-point roll cage is mandatory. All bars must be welded and be a minimum diameter of 1 ½" and minimum .083 wall thickness steel tubing. No pipe fittings are allowed. Aluminum and other soft materials are not permitted.
- 2. Drivers-side door must be hulled out for roll cage only.
- 3. Must have a full-containment seat or Hans device or Hybrid device. If these are not being used, a 50 lb penalty will apply.

- 4. All cars must have 3" lap belt and 2" shoulder harness and crotch strap MINIMUM and must be attached to roll cage.
- 5. Steering wheel center must be padded.
- 6. A fuel cell may be used. If so, it must be mounted inside a 0.20 gauge metal box secured by 1" steel straps.
- 7. Complete fire suits and Snell rated helmets are required.
- 8. Raceceivers are mandatory.
- All cars must be equipped with a fully charged 2 lb minimum fire extinguisher that is in good working condition. The extinguisher must be mounted within easy reach of the driver.
- 10. All cars must be equipped with a cut-off switch.

## WHEELS:

- 1. 7" maximum width wheels, 1" tolerance. May be double centered.
- 2. Oversized lug nuts are recommended.

## TIRES:

- 1. Maximum tire size is P235/70R15. DOT tires only.
- 2. No racing tires are allowed.
- 3. All four wheels must be the same (14", 15", etc.).

## **WEIGHT:**

- 1. After the race, the car must weigh 1 lb. per c.c.
- 2. Minimum weight of 2200 lbs for all cars/drivers.